



1 Doppio collettore di raffreddamento per ottimo rendimento.

2 Robusto carter paracinghia in metallo.



3 Piedi fissi con antivibranti.



GS38/500/850/PF/T

500

MODELLO Model	CODICE Code														€		
		Litri Liters	Litri/min Liters/min	CFM	min-1	Cilindri Cylinders	Stadi Stages	bar	psi	kW	HP	Volt	Hz	dB/A		L x P x H cm	Kg
GS35/500/600/PF/T	AF 038	500	600	21,2	1.450	2	2	11	159	4	5,5	400	50	78	198x60x125	210	2.239,00
GS37/500/660/PF/T	AF 039	500	660	23,5	1.450	2	2	11	159	4	5,5	400	50	78	198x60x120	216	2.328,00
GS38/500/650/PF/T	AF 040	500	655	23	900	2	2	11	159	4	5,5	400	50	76	198x60x132	238	2.682,00
GS38/500/850/PF/T	AF 041	500	850	30	1.150	2	2	11	159	5,5	7,5	400	50	76	198x60x132	250	2.758,00
GS50/500/920/PF/T	AF 042	500	913	32	850	2	2	11	159	5,5	7,5	400	50	77	198x60x142	295	3.385,00
GS50/500/1200/PF/T	AF 043	500	1.182	42	1.100	2	2	11	159	7,5	10	400	50	77	198x60x142	320	3.461,00
GS80/500/1250/PF/T	AF 044	500	1.236	43,6	850	4	2	11	159	7,5	10	400	50	78	198x60x140	330	4.586,00
GS80/500/1600/PF/T	AF 045	500	1.600	56,5	1.100	4	2	11	159	11	15	400	50	78	198x60x140	350	4.803,00

■ Maggiorazione 15 bar - Overprice for 15 bar - Surprix pour 15 bar - Mehrpreis für 15 bar € 312,00

■ Avviamento stella/triangolo - Star/delta starter - Démarrage étoile/triangle - Stern/Dreieck Anlassen € 465,00