



GS38/100/MOTO



GS25/100/MOTO



1 Manometri inox alla glicerina.



2 Valvola messa a vuoto di grandi dimensioni.



2 Ruote pneumatiche.

24 ÷ 270

MODELLO <i>Model</i>	CODICE <i>Code</i>											€			
		Litri <i>Liters</i>	Litri/min <i>Liters/min</i>	CFM	min-1	Cilindri <i>Cylinders</i>	Stadi <i>Stages</i>	bar	psi	kW	HP		dB/A	L x P x H <i>cm</i>	Kg
GS25/24/MOTO	AI 007	24	500	17,6	1.450	2	1	10	145	4,5	6	79	80x38x75	50	2.181,00
GS25/50/MOTO	AI 110	50	500	17,6	1.450	2	1	10	145	4,5	6	79	90x35x78	60	2.207,00
GS25/100/MOTO	AI 008	100	500	17,6	1.450	2	1	10	145	4,5	6	79	115x40x80	69	2.271,00
GS25/100/DIESEL	AI 009	100	500	17,6	1.450	2	1	10	145	4	5,5	80	115x40x80	84	3.883,00
GS38/100/MOTO	AI 010	100	650	23	900	2	2	11	159	6,7	9	79	115x40x100	108	3.623,00
GS38/200/MOTO	AI 011	200	650	23	900	2	2	11	159	6,7	9	79	150x55x120	132	3.813,00
GS38/270/MOTO	AI 012	270	850	30	1.150	2	2	11	159	10	13,5	79	150x58x125	180	4.310,00
GS38/270/DIESEL	AI 013	270	650	23	900	2	2	11	159	5,5	7,5	80	155x58x125	180	6.001,00
GS50/270/MOTO	AI 014	270	1.000	35,3	900	2	2	11	159	10	13,5	79	155x58x135	210	5.138,00
GS50/270/DIESEL	AI 015	270	1.000	35,3	900	2	2	11	159	7,5	10	83	155x58x135	230	7.625,00

- Avviamento a strappo di serie - Standard recoil start - Démarrage à lanceur standard - Serienmäßig mit Seilzugstarter
- Avviamento elettrico optional a richiesta - Optional electric start on request - Démarrage électrique optionnel sur demande - Elektrisches Anlassen als Sonderzubehör auf Anfrage