

OPK



PRODUCTS DIGEST

— Japan Quality —

FOUNDED 1934



OKUDAYA GIKEN CO., LTD.

OSAKA JAPAN

ESTABLISHED 1954

HAND PALLET TRUCK SERIES

Standard Type



- Capacity : 1500/2000/2500/3000/5000 kg
- Fork (W) : 470/520/685/700 mm
- Fork (L) : 850/1070/1150/1220/1500/1800 mm
- Min. (H) : 80/85/100 mm (STANDARD)
65 mm (LOW PROFILE)
- Max. (H) : 200/205/220 mm (STANDARD)
185 mm (LOW PROFILE)

CP-155-107

Ultra Low Profile Type



- Capacity : 1000/1250 kg
- Fork (W) : 450/520/685 mm
- Fork (L) : 850/1000/1070
1220/1400 mm
- Min. (H) : 39/45 mm
- Max. (H) : 114/135 mm

CPL-105-107



Cold Room Type



- Capacity : 1500/2000 kg
- Fork (W) : 470/520/685 mm
- Fork (L) : 850/1070/1220 mm
- Min. (H) : 65/80 mm
- Max. (H) : 185/200 mm

CPF-155-107-A

Traverse Type



- Capacity : 1500 kg
- Fork (W) : 685 mm
- Fork (L) : 650/850/1070/1220 mm
- Min. (H) : 80 mm
- Max. (H) : 205 mm

CPW-15L-65

HIGH CATCH SERIES

Manual Type



HC-10A-45

- Capacity : 500/1000 kg
- Fork (W) : 520/685 mm
- Fork (L) : 800/930/1070 mm
- Min. (H) : 85 mm
- Max. (H) : 450/700/720 mm

Battery Type



HC-D10A-70

- Capacity : 500/1000 kg
- Fork (W) : 520/685 mm
- Fork (L) : 930/1070 mm
- Min. (H) : 85 mm
- Max. (H) : 700/720 mm

Self-propelled Type



HC-U5A-70

- Capacity : 500 kg
- Fork (W) : 520/685 mm
- Fork (L) : 930 mm
- Min. (H) : 85 mm
- Max. (H) : 720 mm



SANTO CAR SERIES



Table (Standard) Type



- Capacity : 200/400 kg
- Table : (W)540/600 × (L)600/650 mm
- Min. (H) : 160 mm
- Max. (H) : 800/1150 mm

SC-4-12-A

Table (Low Profile) Type

- Capacity : 200/400 kg
- Table : (W)540/600 × (L)600/650 mm
- Min. (H) : 95 mm
- Max. (H) : 730/1080 mm



SC-4-8L-A



Available for Rubber Wheel

Fork Type



- Capacity : 200/400 kg
- Fork (W) : 515/570 mm
- Fork (L) : 600/650 mm
- Min. (H) : 80 mm
- Max. (H) : 720/1070 mm

SC-2-8F-A

Battery Type



- Capacity : 200/400 kg
- Table : (W)540/600 × (L)600/650 mm
- Min. (H) : 160 mm
- Max. (H) : 800/1150 mm

SC-D4-12-A

Roll (SR) Type



SC-2-8SR-1



Roll (R) Type



SC-4-8R-1



- Capacity : 200 kg
- Roller (W) : 480 mm
- Roller (φ) : 60 mm
- Min. (H) : 200 mm
- Max. (H) : 840/1190 mm

- Capacity : 200/400 kg
- Roller (W) : 480/550 mm
- Roller (φ) : 55/76 mm
- Min. (H) : 200/245 mm
- Max. (H) : 840/885/1190/1235 mm

POWER LIFTER SERIES (STANDARD TYPE)



Manual Stacker



PL-H350-15

- Capacity : 350 kg
- Fork (W) : 530 mm
- Fork (L) : 650 mm
- Min. (H) : 80 mm
- Max. (H) : 1500 mm



PL-H500-15

- Capacity : 500/650 kg
- Fork (W) : 575 mm
- Fork (L) : 650/800 mm
- Min. (H) : 80 mm
- Max. (H) : 1500 mm



PL-H1000-15

- Capacity : 1000 kg
- Fork (W) : 725 mm
- Fork (L) : 800 mm
- Min. (H) : 80 mm
- Max. (H) : 1500 mm



PL-H1000-15L

- Capacity : 1000 kg
- Fork (W) : 725 mm
- Fork (L) : 1000 mm
- Min. (H) : 80 mm
- Max. (H) : 1500 mm

Battery Stacker



PL-D500-15

- Capacity : 350/500/650 kg
- Fork (W) : 530/575 mm
- Fork (L) : 650/800 mm
- Min. (H) : 80 mm
- Max. (H) : 1500 mm



PL-D1000-15

- Capacity : 1000 kg
- Fork (W) : 725 mm
- Fork (L) : 800/1000 mm
- Min. (H) : 80 mm
- Max. (H) : 1500 mm



PLW-D650-25

- Capacity : 350/500/650 kg
- Fork (W) : 640/775 mm
- Fork (L) : 650/800 mm
- Min. (H) : 80 mm
- Max. (H) : 2500 mm

Picking Power Lifter



PPLW-D200-27

- Capacity : 200 kg
- Table : (W)625×(L)600 mm
- Min. (H) : 470 mm
- Max. (H) : 2730 mm



POWER LIFTER SERIES (ECONOMY TYPE)

Manual Stacker



PL-H350-12S

- Capacity : 200/350 kg
- Fork (W) : 470/530 mm
- Fork (L) : 550/650 mm
- Min. (H) : 75/80 mm
- Max. (H) : 850/1200
1500 mm



PL-H500-15S

- Capacity : 500/650 kg
- Fork (W) : 575 mm
- Fork (L) : 650/800 mm
- Min. (H) : 80 mm
- Max. (H) : 1500 mm

Battery Stacker



PL-D500-15S

- Capacity : 200/350/500/650 kg
- Fork (W) : 470/530/575 mm
- Fork (L) : 550/650/800 mm
- Min. (H) : 75/80 mm
- Max. (H) : 1200/1500 mm



PLW-D400-21S

- Capacity : 250/400 kg
- Fork (W) : 530/575 mm
- Fork (L) : 650 mm
- Min. (H) : 80 mm
- Max. (H) : 2150 mm

SELF-PROPELLED BATTERY POWER LIFTER



PL-U Type



PL-U350-15

- Capacity : 350/500/650 kg
- Fork (W) : 530/575 mm
- Fork (L) : 650/800 mm
- Min. (H) : 80 mm
- Max. (H) : 1500 mm

PL-S Type



PL-S800-15

- Capacity : 500/650/1000 kg
- Fork (W) : 725/775 mm
- Fork (L) : 650/800 mm
- Min. (H) : 80 mm
- Max. (H) : 1500/2500 mm

PL-SU Type



PL-SU800-15

- Capacity : 500/650/1000/1500 kg
- Fork (W) : 575/725/800 mm
- Fork (L) : 650/800/1000 mm
- Min. (H) : 80 mm
- Max. (H) : 1400/1500 mm

PLW-SU Type



PLW-SU650-25

- Capacity : 400/500/650/800 kg
- Fork (W) : 775/825 mm
- Fork (L) : 650/800/1000 mm
- Min. (H) : 80 mm
- Max. (H) : 2500 mm

LIFT TABLE SERIES (CADDIE)



Manual Type



LT-H150-7S

- Capacity : 150 kg
- Table : (W)700×(L)400 mm
- Min. (H) : 210 mm
- Max. (H) : 740 mm

LT-H150-7 (Foldable)

- Capacity : 150 kg
- Table : (W)700×(L)400 mm
- Min. (H) : 210 mm
- Max. (H) : 740 mm

LT-H250-8S

- Capacity : 250 kg
- Table : (W)800×(L)500 mm
- Min. (H) : 245 mm
- Max. (H) : 850 mm

LT-H250-8

- Capacity : 250 kg
- Table : (W)800×(L)500 mm
- Min. (H) : 245 mm
- Max. (H) : 850 mm



LT-H550-9L

- Capacity : 550 kg
- Table : (W)900×(L)600 mm
- Min. (H) : 330 mm
- Max. (H) : 980 mm



LT-H800-10

- Capacity : 800 kg
- Table : (W)1000×(L)600 mm
- Min. (H) : 340 mm
- Max. (H) : 1070 mm



LT-WH300-15-A

- Capacity : 300 kg
- Table : (W)900×(L)600 mm
- Min. (H) : 410 mm
- Max. (H) : 1500 mm

Battery Type



LT-D550-9L

- Capacity : 550/800 kg
- Table : (W)900/1000 ×(L)600 mm
- Min. (H) : 330/340 mm
- Max. (H) : 950/1040 mm

Wakie Type



LT-U550-9L

- Capacity : 550/800 kg
- Table : (W)900/1000 ×(L)600 mm
- Min. (H) : 330/340 mm
- Max. (H) : 950/1040 mm

Antyac SERIES

Self-propelled Battery Pallet Truck Type



- Capacity : 1300/1600
1800/2000 kg
- Fork (W) : 620 mm
- Fork (L) : 1070 mm
- Min. (H) : 80 mm
- Max. (H) : 200 mm



SELF-PROPELLED BATTERY PALLET TRUCK

Self-propelled Battery Power Lifter Type



APL-1000-15

- Capacity : 1000/1500 kg
- Fork (W) : 725/800 mm
- Fork (L) : 800/1000 mm
- Min. (H) : 80 mm
- Max. (H) : 1400/1500 mm



APLW-650-25

- Capacity : 650 kg
- Fork (W) : 825 mm
- Fork (L) : 800 mm
- Min. (H) : 80 mm
- Max. (H) : 2500 mm



CPHR-10S-A

- Capacity : 1000 kg
- Fork (W) : 580 mm
- Fork (L) : 1070 mm
- Min. (H) : 80 mm
- Max. (H) : 200 mm



STAINLESS / ALUMINUM SERIES

All Stainless Pallet Truck



CPFS-15S-107-A

- Capacity : 1500 kg
- Fork (W) : 470/520/685 mm
- Fork (L) : 850/1070/1220 mm
- Min. (H) : 65/80 mm
- Max. (H) : 185/200 mm

Stainless Power Lifter



PL-H350-15SU

- Capacity : 350 kg
- Fork (W) : 530 mm
- Fork (L) : 650 mm
- Min. (H) : 80 mm
- Max. (H) : 1500 mm

Stainless Lift Table



LT-H550-9SU

- Capacity : 250/500 kg
- Table : (W)800/900 × (L)500/600 mm
- Min. (H) : 245/330 mm
- Max. (H) : 850/980 mm

Aluminum Lifter "K LIFTER"



KL-P100-12F

- Capacity : 100 kg
- Table : (W)480/550 × (L)500 mm
- Min. (H) : 160 mm
- Max. (H) : 1000/1200 mm

TILT LIFTER



RL-H50

- Capacity : 500/1000 kg
- Fork (W) : 585 mm
- Fork (L) : 800 mm
- Min. (H) : 90 mm
- Max. (H) : 905/910 mm

DRUM PORTER / DRUM HANDLER

- Capacity : 300 kg
- Turn : 180°
- Lifting(H) : 0-1000 mm (135° TURN)
1250 mm (90° TURN)



CD-250



PL-H300-12DT

- Capacity : 250 kg
- Lifting(H) : 330 mm

BOX LIFTER SERIES

Standard Type

- Capacity : 150 kg
- Fork (W) : 450 mm
- Fork (L) : 500 mm
- Min. (H) : 70 mm
- Max. (H) : 850/1200 mm



BL-H150-8

"L" Fork Type

- Capacity : 150 kg
- Fork (W) : 450 mm
- Fork (L) : 650 mm
- Min. (H) : 7 mm
- Max. (H) : 787/1137 mm



BL-H150-8L

FLOOR CRANE



OC-H500



- Capacity : 500 kg
- Arm (L) : 1100-1550 mm
- Lifting(H) : 2500-2840 mm

As of January 2008

Created by Highly Experienced Hydraulic Equipment Makers.

Originality Produces Know-how

O.P.K. OKUDAYA GIKEN CO., LTD.

285 Tanjo, Mihara-ku, Sakai-city,
Osaka 587-0011, JAPAN.
TEL 81-723-61-7861 FAX 81-723-62-2102

URL : <http://www.opk.co.jp>



REGISTERED ORGANIZATION
NO.0989-ISO9001
NO.E933-ISO14001
Acquired by head office



QS Accreditations
R002, R002



This pamphlet was printed with
environment-friendly soy-based ink on
recycled paper.

* Products with special specifications besides those with standard specifications are manufactured as well. Feel free to contact OKUDAYA GIKEN.
* The specifications described in this catalog are subject to change without notice for product improvement.
* The colors of actual products may be more or less different from those printed in this catalog.

All rights reserved.