



## Sanders

### 6 Inch DUAL ACTION SANDER

This dual action sander is ideal for general sanding and body work. Use for feather edging, surface preparation, and finish work.

- Ball bearing construction for smooth performance and long life
- Spins at 10,000 RPM, 3/8 in. orbit
- Built-in regulator for speed control

### 5 Inch RANDOM ORBITAL SANDER

The CL1565 produces a swirl-free fine finish and is a great tool for surface preparation.

- Soft palm grip for operator comfort
- Lightweight, composite housing design
- Single lever variable speed regulator

CL156500 - PSA Pad / CL156570 - Hook & Loop

### 6 Inch RANDOM ORBITAL SANDER

The CL1567 produces a swirl-free fine finish and is a great tool for surface preparation.

- Soft palm grip for operator comfort
- Lightweight, composite housing design
- Single lever variable speed regulator

CL156700 - PSA Pad / CL156770 - Hook & Loop Pad

#### CL1504

Pad Size	6-in.
Spindle Thread	5/16-24
Free Speed RPM	10,000
Air Consumption Avg.	16.5 SCFM
Air Consumption Cont.	23.1 SCFM
Air Inlet	1/4-in. NPT
Min. Hose Size	3/8-in.
Weight	3.5 lbs.

#### CL156500/CL156570

Pad Size	5-in.
Spindle Thread	5/16-24
Free Speed RPM	10,000
Air Consumption Avg.	13.7 SCFM
Air Consumption Cont.	19.6 SCFM
Air Inlet	1/4 in. NPT
Min. Hose Size	3/8-in.
Weight	1.8 lbs.

#### CL156700/CL156770

Pad Size	6-in.
Spindle Thread	5/16-24
Free Speed RPM	10,000
Air Consumption Avg.	13.7 SCFM
Air Consumption Cont.	19.6 SCFM
Air Inlet	1/4-in. NPT
Min. Hose Size	3/8-in.
Weight	1.8 lbs.

## Air Hammer

### AIR HAMMER

The CL1543 delivers 3,500 blows per minute for fast and powerful cutting action. Ideal for automotive exhaust work and general cutting, chipping, and scraping.

- Coil spring retainer for quick chisel changes
- 2-5/8 inch stroke length
- Accepts 0.401 round shank chisels

#### CL1534

Stroke	5/8-in.
Blows/Min.	3,500
Chisel Shank	0.401-in.
Air Consumption Avg.	11 SCFM
Air Consumption Cont.	18.4 SCFM
Air Inlet	1/4 in. NPT
Min. Hose Size	3/8-in.
Weight	3.5 lbs.

## Reciprocating Saw

### RECIPROCATING SAW

The CL1540 reciprocating saw cuts through materials with ease. An excellent tool for body, exhaust and muffler work.

- Two blades included, 24T and 32T, to cut a variety of materials.
- Adjustable blade guard also acts as tool guide.

#### CL1540

Strokes/min.	9,000
Stroke	0.4-in.
Air Consumption Avg.	2.2 SCFM
Air Consumption Cont.	8.6 SCFM
Air Inlet	1/4-in. NPT
Min. Hose Size	3/8-in.
Weight	1.4 lbs.